

DSM Embedded System

NanoServer® E6



Technical Specifications

DSM Embedded Controller

- up to 4 GB DDR RAM, 667 MHz, 0 MB equipped
- Intel® 82945GM Chipset
- 1 x 10/100 Base-TX LAN, Intel® 82562ET
- 1 x 1000 Base-T LAN, Marvell 88E8053 PCI-Express
- opt. Wireless LAN 802.11b/g
- Intel® Graphic Media Accelerator 950 VGA, with 224 MB shared memory, max. resolution 1600 x 1200 @ 85 Hz, S-VIDEO and Composite TV-Out
- Audio Controller, AC'97, S/PDIF and Line-Out
- Serial ATA for 2 SATA II 300 drives
- Controller with one IDE port (2 x EIDE devices)
- opt. Disk-on-Module or Compact Flash
- two serial port, IEEE 1394 TI TSB43LV22 1 Port FireWire
- 6 x USB 2.0 (4 x ext., 2 x int.), PS/2 Port (2x)
- 1 x Mini-PCI slot (internal), Typ IIIA

Optional 2 x PCI or 1 x PCI and 1 x PCI Express x1 expansion slot for half-size cards

Drive bay for two 2.5" HDD, SATA II 300 Floppy / CD/DVD-ROM through USB 2.0 ext. possible

Solid high-quality industrial Case

- Case in all RAL and NCS color available
- On request also with your corporate logo
- Control LEDs
- Power supply: - ext. 70 Watt power supply, 100-240 Volt AC
- or direct over 12 Volt DC
- incl. mounting rails
- Dimensions WxDxH: 206 x 220 x 110 mm

1 year Warranty, 48-hour Burn-In, CE Certification

96M1558 DSM Embedded System "NanoServer® E6"

- Intel® Core™ Duo T2500, 2.0 GHz with cooler fan
- incl. 4 cm system cooler fan
- opt. 8 - 30 Volt DC (92 Watt) power supply
- **Operating Temperatures: 0° - +50°C**

**Optional 2 x PCI or
1 x PCI and 1 x PCI Express x1**



**Custom
configurations/CPU's
on request!**



DSM[®] Computer

DSM Computer AG
Industrial Park
Am Loferfeld 50-54
81249 Munich, Germany
Tel.: +49 (0)89-15798-250
Fax: +49 (0)89-15798-196
www.DSM.AG
info@DSM.AG

Layout for 96M1558

