

## NanoServer® E3



### Technical Specifications

#### DSM Embedded Controller

- up to 1 GB DDR RAM, 333 MHz, 0 MB equipped
- Intel® 82855 GME Chipset
- 1 x 10/100 Base-TX LAN, Intel® 82801DB
- 1 x 1000 Base-T LAN, Intel® 82541ER
- opt. Wireless LAN 802.11b/g
- Intel® Extreme Graphics 2 VGA with 64 MB shared memory, MPEG2-Decoder, max. resolution 1600 x 1200 @ 85 Hz
- Audio Controller, AC'97
- Controller with 2 IDE ports (4 x EIDE devices)
- opt. Disk-on-Module or Compact Flash
- two serial port, one parallel port
- 6 x USB 2.0 (4 x ext., 2 x int.), PS/2 Port (2x)
- 1 x Mini-PCI slot (internal), Typ IIIA

#### Optional 2 x PCI expansion slot for half-size cards

#### Drive bay for one 2.5" HDD, Ultra DMA/33/66/100 Floppy / CD/DVD-ROM through USB 2.0 ext. possible

#### Solid high-quality industrial Case

- Case in all RAL and NCS color available
- On request also with your corporate logo
- Control LEDs
- Power supply: - ext. 70 Watt power supply, 100-240 Volt AC - or direct over 12 Volt DC
- incl. mounting rails
- Dimensions WxDxH: 206 x 220 x 110 mm

#### 1 year Warranty, 48-hour Burn-In, CE Certification

#### 96M1560 DSM Embedded System "NanoServer® E3"

- Intel® Pentium® M 1.8 GHz with cooler fan
- incl. 4 cm system cooler fan
- opt. 8 - 30 Volt DC (92 Watt) power supply
- **Operating Temperatures: -10° - +50°C**

#### 96M1560L DSM Embedded System "NanoServer® E3"

- Intel® Pentium® M 1.4 GHz **Fanless**
- **Operating Temperatures: -10° - +60°C \***


#### 96M1560C DSM Embedded System "NanoServer® E3"

- Intel® Celeron® M 1.3 GHz with cooler fan
- incl. 4 cm system cooler fan
- opt. 8 - 30 Volt DC (92 Watt) power supply
- **Operating Temperatures: -10° - +50°C**

### Optional 2 free PCI expansion slots



**Custom configurations/CPU's on request!**



# DSM<sup>®</sup> Computer

**DSM Computer AG**  
Am Loferfeld 54  
81249 Munich, Germany  
Tel.: +49 (0)89-15798-250  
Fax: +49 (0)89-15798-196  
www.DSM.AG  
info@DSM.AG

### Layout for 96M1560-1560L-1560C

